









FLEX · 365-385W
MWT Mono PERC Flexible Module

21.8%

Module efficiency up to 21.8%


Features

- 
Light, Thin design
 6.3kg weight, 2.5mm thickness, match various requirements for low-load projects
- 
Ultra Flexible
 Ultra-thin silicon wafers with advanced organic polymer encapsulation materials, minimum bending radius reach 0.30m, fit all kinds of curved surface perfectly
- 
High Efficiency And Reliability
 Busbar-free design increases cell conversion efficiency, more power output can be achieved at low irradiance conditions
- 
Customizable
 Customized design for different scenarios
- 
Convenient Installation
 Easy installation and convenient transportation with lower cost
- 
Lead-free
 Eco-friendly PV design achieves lead-free MWT module without soldering materials

Reinsurance Coverage for 25 Years



Insured by LLOYD'S
LLOYD'S



※1st year degradation less than 2.5%, 25 years power output 82.36% guaranteed.

Comprehensive Qualifications & Certifications

- ★ ISO 9001: 2015 Quality Management System
- ★ ISO 14001: 2015 Environment Management System

- ★ ISO 45001: 2018 Occupation Health Safety Management System



Electrical Characteristics at Standard Test Conditions(STC)

Spec/Model	Unit	SP-365Q	SP-370Q	SP-375Q	SP-380Q	SP-385Q
Max-Power(Pm)	W	365	370	375	380	385
Power Tolerance	W			0~+5		
Max-Power Voltage(Vm)	V	34.9	35.1	35.3	35.5	35.7
Max-Power Current(I _m)	A	10.46	10.54	10.62	10.70	10.78
Open-Circuit Voltage(Voc)	V	42.4	42.6	42.8	43.0	43.2
Short-Circuit Current(I _{sc})	A	11.09	11.16	11.23	11.30	11.35
Effective Module Efficiency(η _m)	%	20.7	21.0	21.2	21.5	21.8

STC: AM=1.5, Irradiation 1000W/m², Module Temperature 25°C

Electrical Characteristics at Nominal Module Operating Temperature (NMOT)

Spec/Model	Unit	SP-365Q	SP-370Q	SP-375Q	SP-380Q	SP-385Q
Max-Power(Pm)	W	274	278	282	286	290
Max-Power Voltage(Vm)	V	32.8	33.0	33.2	33.4	33.6
Max-Power Current(I _m)	A	8.35	8.42	8.49	8.56	8.64
Open-Circuit Voltage(Voc)	V	39.9	40.1	40.3	40.5	40.7
Short-Circuit Current(I _{sc})	A	8.91	8.98	9.05	9.12	9.19

NMOT: Irradiation 800W/m², Ambient temperature 20°C, Wind Speed 1m/s

Temperature Coefficient

Nominal Module Operating Temperature	43±2°C
Temperature coefficient of P _{max}	-0.36%/°C
Temperature coefficient of Voc	-0.28%/°C
Temperature coefficient of I _{sc}	0.06%/°C

Operating Conditions

Max. system voltage	DC1500V(IEC)
Max. series fuse rating	18A
Operating temperature range	-40°C~+85°C


Mechanical Characteristics

Installation Module Dimension (L×W×H)	1840mmx1040mmx2.5mm
Actual Module Dimension(L×W)	1763mmx1001mm
Weight	6.3 kg
Back material	Back Sheet(white)
Cell (quantity / material / type / dimensions)	126(21x6) / Mono / Half-cell
Encapsulant	POE
Frame	None
Junction box(protection degree)	IP68
Cable (length/cross-section area)	Customizable / 4mm ²
Connector	MC4 Compatible
Bending radius	0.3m

Package


Transportation	Container Size	Quantity(pcs)	Quantity(per pallet)
Container	40' HQ	1104	46
Platform Trailer	13m	1196	46
Platform Trailer	17.5m	1564	46

Module Size



I-V Curve

I-V Curves of SP-375Q at different irradiance



I-V Curves of SP-375Q at different cell temperature

